


NEW
Upgraded
375 Lbs.
Duty Rating

6300SERIES



Tool-Tra-Top® with drill holster



Internal steel spreaders



Molded external rail shield to protect against abrasion damage

Internal spreaders

Double riveted step construction

Model 6306 Shown

★ ★ ★ ★ ★
375 lbs. LOAD CAPACITY

Combined Weight of User and Materials

Type IAA Duty Rating

THE
EDGE™
ENERGY DIFFUSING GEOMETRY

Provides enhanced bracing strength and increased protection against damage





6300SERIES

Extra Heavy Duty Fiberglass Stepladders

375lbs. Load Capacity
Special Duty/Professional Use **TYPE IAA**
DUTY RATING

- Molded Tool-Tra-Top® with drill holster and convenient tray for tools
- Internal steel spreaders
- Double riveted aluminum steps are deeply serrated for Traction-Tred®
- Molded external rail shields help protect against abrasion damage
- EDGE® molded brace and foot pad combination provides enhanced bracing strength and increased protection against damage



6' FIBERGLASS STEPLADDER
MODEL 6306

NEW Duty Rating

★★★★★
375 lbs. LOAD CAPACITY
Combined Weight of User and Materials

Type IAA Duty Rating

SPECIFICATIONS 6300 Series

Model No.	Size	Approx. Width	Approx. Spread	Approx. Cu. Ft. Per Unit	Approx. Ship Wt. Lbs.	Load Capacity†
6303	3'	18-1/8"	23-1/8"	2.0	13.0	375 lbs
6304	4'	19-7/8"	29"	3.0	16.0	375 lbs
6305	5'	21-5/8"	35-1/4"	4.1	19.0	375 lbs
6306	6'	23-3/8"	41-1/4"	5.3	22.0	375 lbs
6308	8'	26-7/8"	53-1/2"	8.1	30.0	375 lbs
6310	10'	30-3/8"	65-7/8"	12.5	38.0	375 lbs
6312	12'	33-7/8"	78-1/4"	15.0	48.0	375 lbs

† Load capacity combines the total weight of both the user and the materials.

DIMENSIONS

Top:	5-3/4" x 13"	Steps:	3" wide
Front Rails:	3-1/8" wide	Rear Rails:	1-7/8" wide
Flange:	1-3/16" wide	Flange:	1-3/16" wide



GM6540 ©2005 WERNER CO. February 2005